



INNOVATIVE AND ELEGANT FROM EDGE TO BASE.



E2461FWH

61
SERIES
SUPER NARROW BEZEL

- ◆ Ultra Slim
- ◆ Narrow Border Design
- ◆ Clear Vision
- ◆ Green Display with LED Panel
- ◆ Ultra High DCR (50M:1)



■ Features



LED Panel: Hg Free

Mercury (Hg) is poisonous, producing toxic environmental waste. Unlike the CCFL backlight in traditional monitors, the LED backlight panel contains no Hg.



Dynamic Contrast Ratio (DCR)

Ultra-high Dynamic Contrast Ratio of 50,000,000:1 displays darker images with more depth and detail.



Ultra Low Power Consumption

The LED backlight panel requires 50% less energy than typical 4CCFL monitors.



Clear Vision

The image performance engine can upscale Standard Definition (SD) sources to High Definition (HD) for sharper, more vivid viewing.



Multimedia-Ready with HDMI Input

HDMI (High-Definition Multimedia Interface) is the digital video and sound standard for connecting the latest consumer electronics like Blu-ray players and game consoles (for E2261FWH/E2461FWH only).



e-Saver

Software enables the user to set a low power configuration of the monitor when the PC is in screen saving, PC off, and user absence. User can choose the time to turn the monitor off, to save power consumption.



Off Timer

To save power, a timer can be set to automatically turn off the monitor after a user-defined interval.



i-Menu

Included PC software allows the user to change the OSD settings using their mouse.



Eco Mode

Hotkey adjustment of display settings suit 5 different viewing styles: Text, Internet, Game, Movie and Sport.



Energy Star®

■ Specifications

Model Name	E2461FWH
Screen Size	23.6"W
Viewable Image Size	598mm
Pixel Pitch	0.2715(H)×0.2715 (V)mm
Display Area	521.28(H)×293.22(V)mm
Brightness	250 cd/m ²
Typical Contrast Ratio	1,000:1
Contrast Ratio	50,000,000:1 (DCR)
Response Time (typical)	2ms
Viewing Angle	170/160 (CR≥10)
Scan Frequency	H: 30K~83KHz V: 50~76Hz
Pixel Frequency	170MHz
Recommended Resolution	1920×1080@60Hz
Display Colours	16.7M
HDCP Compatible	Yes
Input Signal	Analog RGB and HDMI
Input Connector	15-pin D-Sub and HDMI
Power Supply	100~240VAC, 50/60Hz
Power Consumption	Power On: <24W (Typical), Standby: <0.5W
Plug & Play	VESA DDC2B™ & DDC2B/CI
User Control	Auto/Source/Exit; Clear Vision/<; Volume(4:3wide)/>;Menu, Power
OSD Languages	16 languages
Speakers	No
Safety & Regulations	CCC, CEL-1, China Rohs, FCC, CE/CB, cTUVus, TUV-S, TUV-Bauart, KCC, Windows 8, ISO9241-307, EPA, C-Tick, EU RoHS Doc, BSMI, TCO6.0, REACH DoC, CQC, VCCI, J-moss, e-standby, Energy star, Ukarin safety, GOST, NOM, Eup, WEEE
Wall-Mount	75mm×75mm
Cabinet Colour	Black & Red
W×H×D (w/base)mm	545.5×401.5×214.5 mm
W×H×D (package)mm	606×120×420mm
Weight (Net /Gross)	3.95Kg/4.85Kg