



Art Of Colors



52-Series LED Monitor

- LED Wide View Monitor
- Power Off Timer
- Ultra Real Contrast 5000:1
- Ultra High DCR: Stunning 20million:1
- Multi-function with HDMI
- EPA Energy Star
- Clear Vision



M2752VH



■ Features



LED Panel: Hg Free

Mercury (Hg) is poisonous, producing toxic environmental waste. Unlike the CCFL backlight in traditional monitors, the LED backlight panel contains no Hg.



Dynamic Contrast Ratio (DCR)

Ultra-high Dynamic Contrast Ratio of 20,000,000:1 displays darker images with more depth and detail.



High Contrast-Images more sharp

High contrast ratio images look more brighter,detailed, vivid and sharper.



High Real CR 5000:1



e-Saver

Software enables the user to set low power configuration of monitor when PC is in screen saving, PC off, and user absence. User can choose the time to turn the monitor off, to save power consumption.



Multimedia-Ready with HDMI & DisplayPort Inputs

HDMI (High-Definition Multimedia Interface) is the digital video and sound standard for connecting the latest consumer electronics like Blu-ray players and game consoles. DisplayPort is the latest digital standard with more advanced features.



Eco Mode

Hotkey adjustment of display settings suit 5 different viewing styles: Text, Internet, Game, Movie and Sport.



Ultra Slim with Hidden Controls

Control buttons are discreetly concealed to enhance the streamlined and stylish design.



4ms Response Time

Fast 4ms (GTG) screen response displays moving images without blurring.



Clear Vision

The image performance engine can upscale Standard Definition (SD) sources to High Definition (HD) for sharper, more vivid viewing.



Off Timer

To save power, a timer can be set to automatically turn off the monitor after a user-defined interval.

■ Specifications

Model Name	M2752VH
Screen Size	27"W
Viewable Image Size	68.60cm
Pixel Pitch	0.311(H)×0.311 (V)mm
Display Area	597.89(H)×336.31 (V)mm
Brightness	300 cd/m ²
Contrast Ratio (typical)	20,000,000:1 (DCR)
Response Time (typical)	4ms
Viewing Angle	178/178 (CR≥10)
Scan Frequency	H: 30K~83KHz V: 50~76Hz
Pixel Frequency	170MHz
Recommended Resolution	1920×1080@60Hz
Display Colours	16.7M
HDCP Compatible	Yes
Input Signal	Analog RGB, DVI-D, HDMI
Input Connector	15-pin D-Sub, 24-pin DVI, HDMI
Power Supply	110~240VAC, 50/60Hz
Power Consumption	Power On: <60W (Typical), Standby: <0.5W
Plug & Play	DDC 2B/C1 & VESA DDC2B™
User Control	Clear Vision/-,Volume/+, Source/Auto/Exit, Power,Menu
OSD Languages	16 languages
Speakers	2.0W x2
Safety & Regulations	FCC, cCSAus, CE, EPA, ROHS, ISO9241-307, Windows 7, BSMI,
Wall-Mount	100mm x 100mm
Cabinet Colour	Black
Mechanical Function	Tilt: -4°~17°
W×H×D (w/base)mm	645.7×452×210
W×H×D (package)mm	714×520×131
Weight (Net /Gross)	5.287Kg/6.94Kg

Design and Specifications are subject to change without notice.